

Application Number 10/813,495
Responsive to Office Action mailed March 23, 2006

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A ~~servo writing apparatus~~ system comprising:
a servo writing apparatus that includes a first servo write head comprising a first write gap to substantially magnetize magnetic particles of magnetic tape in a first direction; and a second servo write head comprising one or more second write gaps arranged to define a time-based servo pattern magnetized in a second direction on the magnetic tape, wherein the first write gap and the second write gaps define a servo channel corresponding to a servo band on the magnetic tape; and wherein
an alignment tool that translates and rotates the first and second servo write heads to substantially align the first write gap and the second write gaps ~~are substantially aligned~~ in the servo channel to within less than 10 micrometers.
2. (Currently Amended) The ~~servo writing apparatus~~ system of claim 1, further comprising a shield between the first servo write head and the second servo write head.
3. (Currently Amended) The ~~servo writing apparatus~~ system of claim 1, wherein the time-based servo pattern defined by the one or more second write gaps substantially corresponds to one of an N-shaped pattern, a “/ \”-shaped pattern, a “\ /”-shaped pattern, a “< >”-shaped pattern, a “//// \\\”-shaped pattern, a “\\ \\\”-shaped pattern, and a “<<<< >>>>”-shaped pattern.
4. (Currently Amended) The ~~servo writing apparatus~~ system of claim 1, wherein the first servo write head comprises a plurality of first write gaps and the second servo write head comprises a plurality of second write gaps, and wherein each of the plurality of first write gaps

Application Number 10/813,495
Responsive to Office Action mailed March 23, 2006

aligns with corresponding second write gaps of the plurality of second write gaps to define a plurality of servo channels.

5. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 4, wherein each of the plurality of servo channels corresponds to a servo band and each of the plurality of servo channels is separated by a distance corresponding to at least a width of a data track, wherein the width of each of the data tracks is less than 18 micrometers and the width of each of the servo bands is less than 190 micrometers.

6. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 1, wherein the first servo write head comprises a first coil controlled to provide a direct current (DC) magnetic field across the first write gap and the second servo write head comprises a second coil controlled to provide magnetic field pulses across the second write gaps.

7. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 1, wherein the first servo write head comprises a first core and the second servo write head comprises a second core, wherein the cores are bonded to each other.

8. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 1, wherein the second servo write head comprises a surface thin film that defines the second write gaps.

9. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 1, further comprising a mounting structure wherein the first and second servo write heads are mounted in the mounting structure.

10. (Currently Amended) The ~~servo-writing apparatus~~ system of claim 8, wherein the mounting structure defines a width and the mounted first and second servo write heads define a separation distance, and wherein a ratio of the mounting structure width to the servo write head separation distance is greater than 2 to 1 and less than 50 to 1.

Application Number 10/813,495
Responsive to Office Action mailed March 23, 2006

11. (Currently Amended) The ~~servo writing apparatus system~~ of claim 8 ~~9~~, wherein the mounted first and second servo write heads define a separation distance greater than 0.7 millimeters and less than 20 millimeters.

12. (Currently Amended) A servo writing apparatus comprising a single core that defines a first servo write head and a second servo write head, wherein the first servo write head comprises a first write gap to substantially magnetize magnetic particles of magnetic tape in a first direction and the second servo write head comprises one or more second write gaps oriented to define a time-based servo pattern magnetized in a second direction on the magnetic tape, wherein the first write gap and the second write gaps define a servo channel corresponding to a servo band on the magnetic tape and wherein the first write gap and the second write gaps are substantially aligned in the servo channel to within less than 10 micrometers.

13. (Currently Amended) The servo writing apparatus of claim 12, further comprising a mounting structure, wherein the single core is mounted in the mounting structure.

14. (Currently Amended) A method comprising aligning a first write gap of a first servo write head that substantially magnetizes magnetic particles of magnetic tape in a first direction and one or more second write gaps of a second servo write head that are arranged to define a time-based servo pattern magnetized in a second direction on the magnetic tape by translating and rotating the first and second servo write heads, such that wherein the first write gap and the second write gaps define a servo channel corresponding to a servo band on the magnetic tape and the first write gap and the second write gaps are aligned in the servo channel to within less than 10 micrometers.

15. (Original) The method of claim 14, wherein aligning the first write gap and the second write gaps comprises aligning the second write gaps to a mount reference surface on a mounting structure and aligning the first write gap to the second write gaps and the mount reference surface.

Application Number 10/813,495
Responsive to Office Action mailed March 23, 2006

16. (Original) The method of claim 15, further comprising using an alignment tool comprising a servo head holder and a microscope objective to individually align the second write gaps and the first write gap to the mount reference surface.

17. (Original) The method of claim 14, further comprising bonding the first servo write head and the second servo write head to each other once the first write gap and the second write gaps are aligned.

18. (Original) The method of claim 14, further comprising mounting the first servo write head and the second servo write head in a mounting structure once the first write gap and the second write gaps are aligned.

19. (Currently Amended) The ~~method~~ servo writing apparatus of claim 14 ~~12~~, wherein the first servo write head and the second servo write head comprise a surface thin film, ~~the method further comprising bonding the first servo write head and the second servo write head to each other and forming the first write gap and the second write gaps~~ are formed in the surface thin film.

20. (Currently Amended) The ~~method~~ servo writing apparatus of claim 19, wherein ~~forming the first write gap and the second write gaps~~ are formed in the surface thin film ~~includes using a single mask to create the first write gap and the second write gaps.~~